

TECTHERM




ECO UC 44 lb THERMAL PAPER



TH1 Hot Melt Adhesive



GLASSINE RELEASE LINER 40#



Economical 44 lb uncoated direct thermal paper label engineered for budget-friendly, ribbon-free printing in high-volume dry environments. Produces crisp barcodes and text, paired with TH1 aggressive hot melt adhesive for fast bonding to corrugated packaging, cartons, and warehouse bins on a 40# glassine liner.

FACESTOCK

Economy Uncoated Direct Thermal Paper (65 g/m ²)	Caliper (mil) / (μm) ISO 534	Weight (lb) / (g/m ²) ISO 536	Finish Gloss Level (@60°)	Brightness (%) ISO 2470
	2.65 / 67 ±5%	44/65 ±5%	6 ± 2	≥85%

ADHESIVE

TH1 Hot Melt Adhesive	Caliper (oz / gram)	Initial Tack (N/in) FTM 9 (Glass)	90° Peel Adhesion (N/in) FTM 2 (Steel)	Shear Resistance 9.8N/in ² (hours) FTM 3	Min Application Temperature (°F) / (°C)	Service Temperature Range (°F) / (°C)
	0.57 / 16	≥17	≥9 or broken	≥10	32 / 0	(-4 to 176) / (-20 to 80), * For Direct Thermal, service Temp is up to 60 °C

Liner

GLASSINE RELEASE LINER 40#	Caliper (mil) / (μm) ISO 534	Weight (lb) ISO 536	Release Force (gf)
	2 / 52 ±4%	40#	10-35

STORAGE INFORMATION

Store at 23 (±2) °C and 50 (±5) % Relative Humidity.

PRINTING PROCESSES

Flexo / Letter Press (Yes), Offset (Yes), Screen Printing (Yes), Thermal Transfer (No), Direct Thermal (Yes), UV Inkjet (Yes), Laser / Toner (No), HP Indigo (Topcoat / Primer Required).

All information contained in this document is based on measurements, tests and trials commonly used in the industry, but does not constitute a guarantee. All Tecnia materials are sold considering that the buyer has already carried out tests and approved the material for its use and the final use of its customer. All Tecnia materials have a 12-month warranty, counting from the issuance of the sales invoice, regarding possible manufacturing defects, with liability being limited to the value of the material itself, in the quantity that presents a proven defect.